



**MOTOROLA**

TWO-WAY RADIOS

# GP1280: The Sophisticated Radio

The GP1280 is for professionals who need to communicate using the highest levels of MPT radio sophistication. With the efficiency and productivity of the GP1280, it's a sophisticated communication tool in the palm of your hand.



As Dedicated As You Are

Professional Radio

## A wide array of features include:

- **Signalling**  
*The fully compliant MPT signalling package includes MPT1343, Regionet 43 and ANN modes of operation. Radios are configurable for up to 60 personalities including Talkgroup Select and Conventional signalling.*
- **Data Messaging and MAP27**  
*Includes a built-in pager with the capability of sending or receiving a data message*
- **Voice Storage**  
*- Voice Recorder: a paperless notepad allowing you to store and retrieve messages.  
- Voice Message: a voice prompt for callers to leave a message to be stored in the radio.*
- **X-Pand™ Voice Compression and Low Level Expansion**  
*Crisp, clear and strong audio quality in virtually any noisy environment. Low level expansion allows further improvements in audio quality by reducing noise usually heard during pauses in conversation.*
- **Wideband and Programmable Channel Spacing**  
*Provides flexibility in deployment and stocking.*
- **User Information**  
*This large 4-line alpha-numeric display contains a battery gauge and signal quality indicator and provides separate distinctive tones plus name decode for many incoming calls.*
- **Ease of Use**  
*Rapidcall™ - one touch dialling, easy to use menus and an alpha-numeric phonebook/contact list make the full power of GP1280 simple and intuitive to use.*
- **Dynamic Regrouping**  
*Provides over-the-air reconfiguration of the radio plus download of group identity in a meaningful alpha-numeric form.*
- **Missed Call Alerts**  
*The radio can store incoming caller identities, status, and voice messages when the user is absent, and remind the user of unanswered messages.*
- **Option Board Expandability**  
*You can expand the capabilities of GP1280 by adding option boards.*

Please check with your dealer for availability on specific option boards.



# GP1280 Portable Two-Way Radio Specifications

General Specifications	
Channel Capacity	16 (Conventional Mode)
Power Supply	Rechargeable battery 7.5v
Dimensions: H x W x D (mm)	Height excluding knobs
With standard high capacity NIMH battery	152 x 57.5 x 37.5
With ultra high capacity NIMH battery	152 x 57.5 x 40.0
With NiCD battery	152 x 57.5 x 40.0
With Lilon battery	152 x 57.5 x 33.0
Weight: (gm)	
With Standard high capacity NIMH battery	460
With Ultra high capacity NIMH battery	535
With NiCD battery	485
With Lilon battery	390
Average Battery Life @5/5/90 Cycle:	Low Power      High Power
With Standard high capacity NIMH battery	11 hours      8 hours
With Ultra high capacity NIMH battery	14 hours      11 hours
With NiCD battery	12 hours      9 hours
With Lilon battery	11 hours      8 hours
Sealing:	Withstands rain testing per MIL STD 810 C/D/E and IP54
Shock and Vibration:	Protection provided via impact resistant housing exceeding MIL STD 810-C/D/E and TIA/EIA 603
Dust and Humidity:	Protection provided via environment resistant housing exceeding MIL STD 810 C/D/E and TIA/EIA 603

Portable Military Standards 810 C, D, & E						
Applicable MIL-STD	810C		810D		810E	
	Methods	Procedures	Methods	Procedures	Methods	Procedures
Low Pressure	500.1	1	500.2	2	500.3	2
High Temperature	501.1	1,2	501.2	1,2	501.3	1,2
Low Temperature	502.1	1	502.2	1,2	502.3	1,2
Temp. Shock	503.1	1	503.2	1	503.3	1
Solar Radiation	505.1	1	505.2	1	505.3	1
Rain	506.1	1,2	506.2	1,2	506.3	1,2
Humidity	507.1	2	507.2	2,3	507.3	2,3
Salt Fog	509.1	1	509.2	1	509.3	1
Dust	510.1	1	510.2	1	510.3	1
Vibration	514.2	8,10	514.3	1	514.4	1
Shock	516.2	1,2,5	516.3	1,4	516.4	1,4

Transmitter	
*Frequencies - Full Bandsplit	VHF: 136-174 MHz UHF 1: 403-470 MHz UHF 2: 450-527 MHz
Channel Spacing	12.5/20/25 kHz
Frequency Stability (-25°C to +55°C, +25° Ref.)	±2.5 ppm
Power	136-174: 1-5W 403-470: 1-4W 450-527: 1-4W
Modulation Limiting	±2.5 @ 12.5 kHz ±4.0 @ 20 kHz ±5.0 @ 25 kHz
FM Hum & Noise	-40 dB typical
Conducted/Radiated Emission	-36 dBm <1 GHz -30 dBm >1 GHz
Adjacent Channel Power	-60 dB @ 12.5 kHz -70 dB @ 20/25 kHz
Audio Response (300-3000Hz)	+1 to -3 dB
Audio Distortion	3%

Receiver	
*Frequencies - Full Bandsplit	VHF: 136-174 MHz UHF 1: 403-470 MHz UHF 2: 450-527 MHz
Channel Spacing	12.5/20/25 kHz
Frequency Stability (-25°C to +55°C, +25° Ref.)	±2.5 ppm
Sensitivity (12 dB SINAD) EIA	.25 µV typical
Sensitivity (20 dB SINAD) ETS	.50 µV typical
Intermodulation EIA	70 dB
Adjacent Channel Selectivity	60 dB @ 12.5 kHz 70 dB @ 20/25 kHz
Spurious Rejection	70 dB
Rated Audio	0.5W
Audio Distortion @ Rated Audio	3% typical
Hum & Noise	-40 dB @ 12.5 kHz -50 dB @ 20/25 kHz
Audio Response (300-3000 Hz)	+1 to -3 dB
Conducted Spurious Emission	-57 dBm <1 GHz -47 dBm >1 GHz ETS 300 086

Data for +25°C unless otherwise specified

\* Availability subject to individual country's law and regulations.

Specifications are subject to change without notice and are issued for guidance purposes only.

All specifications listed are typical. Radios meet applicable regulatory requirements.

Conforms to EC directive 89/336/EEC

Complies with ETS 300 113

Contact your local Authorised Motorola Dealer to find out more about how communicating with the Professional Radio series will benefit your organisation.



## The Exporter Cc

Specialising in the Export of Communication Equipment  
 PO Box 3643      Tel: +27 (0)21 851 1700  
 Somerset West      Fax: +27 (0)21 851 1699  
 7129      Skype: "radioexport"  
 South Africa      Email: [exportdc@iafrica.com](mailto:exportdc@iafrica.com)  
[www.radioexport.com](http://www.radioexport.com)

For exceptional performance, reliability and quality, Motorola Original accessories and batteries are the only options. For full details, please refer to the Professional Radio Series Accessories brochure.



Motorola, Professional Radios, As Dedicated As You Are and X-Pand are trademarks of Motorola Inc.  
 © 1998 Motorola, Printed in the United Kingdom  
<http://www.mot.com>