



MOTOROLA

TWO-WAY RADIOS

GP388: The Small Versatile Radio

The GP388 is essential for growing organisations because of its unique versatility. When necessary, the radio can easily be programmed in the field to add or delete features. So, whether it's the harsh environment of a construction site or the elegance of an exclusive hotel, the radio of choice is the Versatile. It's the radio that grows with you.



A wide array of features include:

- **Signalling**
The radio software encompasses Private Line™ and 5-tone selective signalling.
- **Whisper**
Allows a user to speak quietly into a radio and still be heard clearly.
- **Channel Scan**
Allows activity on different communications channels to be monitored and answered.
- **Call Forward**
Allows calls to be forwarded to another radio user if you are unable to answer your calls personally.
- **X-Pand™ Voice Compression and Low Level Expansion**
Crisp, clear and strong audio quality in virtually any noisy environment. Low level expansion allows further improvements in audio quality by reducing noise usually heard during pauses in conversation.
- **User Information**
A 14-character alpha-numeric display contains a battery gauge and provides separate distinctive tones plus name decode for many incoming calls.
- **Voice Operated Transmit (VOX)**
Hands free operation when used with Vox headset accessory.
- **Ease of Use**
Simple menus and an alpha-numeric contact list make the full power of GP388 simple and intuitive to use.
- **Emergency Signalling**
Sends a help signal to a pre-defined person or group of people.
- **Status Calls**
Pre-defined text messages which allow the user to send meaningful messages without talking.
- **Lone Worker**
Added security and safety for individuals who work remotely from their team. The radio enters emergency mode if the user does not respond to the warning signal.



As Dedicated As You Are

Professional Radio

GP388 Portable Two-Way Radio Specifications

| General Specifications | |
|---|---|
| Channel Capacity | 255 |
| Power Supply | Rechargeable battery 7.5v |
| Dimensions: H x W x D (mm) | Height excluding knobs |
| With standard high capacity Lilon battery | 101.5 x 55.5 x 33.0 |
| With ultra high capacity Lilon battery | 101.5 x 55.5 x 38.0 |
| Weight: (gm) | 265 |
| With standard high capacity Lilon battery | 285 |
| With ultra high capacity Lilon battery | |
| Average Battery Life @5/5/90 Cycle: | Low Power High Power |
| With standard high capacity Lilon battery | >9 hours >7 hours |
| With ultra high capacity Lilon battery | >13 hours >10 hours |
| Sealing: | Withstands rain testing per MIL STD 810 C/D/E and IP54 |
| Shock and Vibration: | Protection provided via impact resistant housing exceeding MIL STD 810-C/D/E and TIA/EIA 603 |
| Dust and Humidity: | Protection provided via environment resistant housing exceeding MIL STD 810 C/D/E and TIA/EIA 603 |

| Transmitter | |
|---|---|
| *Frequencies - Full Bandsplit | VHF: 136-174 MHz UHF1: 403-470 MHz |
| Channel Spacing | 12.5/20/25 kHz |
| Frequency Stability (-25°C to +55°C, +25° Ref.) | ±2.5 ppm |
| Power | 136-174: 1-5W 403-470: 1-4W |
| Modulation Limiting | ±2.5 @ 12.5 kHz ±4.0 @ 20 kHz ±5.0 @ 25 kHz |
| FM Hum & Noise | -40 dB typical |
| Conducted/Radiated Emission | -36 dBm <1 GHz -30 dBm >1 GHz |
| Audio Response (300-3000Hz) | +1 to -3 dB |
| Audio Distortion | <5% typical |

| Portable Military Standards 810 C, D, & E | | | | | | |
|---|---------|------------|---------|------------|---------|------------|
| Applicable MIL-STD | 810C | | 810D | | 810E | |
| | Methods | Procedures | Methods | Procedures | Methods | Procedures |
| Low Pressure | 500.1 | 1 | 500.2 | 2 | 500.3 | 2 |
| High Temperature | 501.1 | 1,2 | 501.2 | 1,2 | 501.3 | 1,2 |
| Low Temperature | 502.1 | 1 | 502.2 | 1,2 | 502.3 | 1,2 |
| Temp. Shock | 503.1 | 1 | 503.2 | 1 | 503.3 | 1 |
| Solar Radiation | 505.1 | 1 | 505.2 | 1 | 505.3 | 1 |
| Rain | 506.1 | 1,2 | 506.2 | 1,2 | 506.3 | 1,2 |
| Humidity | 507.1 | 2 | 507.2 | 2,3 | 507.3 | 2,3 |
| Salt Fog | 509.1 | 1 | 509.2 | 1 | 509.3 | 1 |
| Dust | 510.1 | 1 | 510.2 | 1 | 510.3 | 1 |
| Vibration | 514.2 | 8,10 | 514.3 | 1 | 514.4 | 1 |
| Shock | 516.2 | 1,2,5 | 516.3 | 1,4 | 516.4 | 1,4 |

| Receiver | |
|-------------------------------|---------------------------------------|
| *Frequencies - Full Bandsplit | VHF: 136-174 MHz UHF1: 403-470 MHz |
| Channel Spacing | 12.5/20/25 kHz |
| Sensitivity (12 dB SINAD) EIA | .35 µV typical |
| Intermodulation ETS | -65 dB |
| Adjacent Channel Selectivity | 60 dB @ 12.5 kHz 70 dB @ 20/25 kHz |
| Spurious Rejection | 70 dB |
| Rated Audio | 0.5W |
| Audio Response (300-3000 Hz) | +1 to -3 dB |

Data is specified for +25°C unless otherwise stated.

*Availability subject to the laws and regulations of individual countries.

*Availability subject to individual country's law and regulations.

Specifications are subject to change without notice and are issued for guidance purposes only.

All specifications listed are typical. Radios meet applicable regulatory requirements.

Conforms to EC directive 89/336/EEC

Contact your local Authorised Motorola Dealer to find out more about how communicating with the Professional Radio series will benefit your organisation.



The Exporter Cc

Specialising in the Export of Communication Equipment
 PO Box 3643 Tel: +27 (0)21 851 1700
 Somerset West Fax: +27 (0)21 851 1699
 7129 Skype: "radioexport"
 South Africa Email: exportdc@iafrica.com
www.radioexport.com

For exceptional performance, reliability and quality, Motorola Original accessories and batteries are the only options.



Motorola, Professional Radios,
As Dedicated As You Are and
X-Pand are trademarks of Motorola Inc.

© 1998 Motorola, Printed in the United Kingdom
<http://www.mot.com>